



Coating shape sprayed from 10W air cap



Coating shape sprayed from 25W air cap



R-871 Pressure With RC-19B



R-2003 Pressure With RC-19B

Functions and Characteristics

- ◆R-2003 suitable for large area high viscosity paint uses in industries such as shoes, furniture decoration etc.
- ◆R-871 suitable for wall paint(multi-color),super-glue,plaseter.

Model	Type of Feed	Fluid Nozzle Orifice	Air cap	Air Pressure	Air Consum-ption	Fluid Output	Spray Width ±20	Weight
		ømm (in)		kg/cm ² (Mpa)	l/min	ml/min	mm(in)	g(lbs)
R-2003-P20	Pressure	2.0(0.079)	R2	3.0(0.29)	260	350	290(11.42)	480(1.06)
R-2003-P25		2.5(0.098)	W2		360	440	300(11.81)	
R-871-10W	Pressure	2.5(0.098)	10W	3.0-4.0(0.29-0.39)	140	440	100-250(3.94-9.84)	505(1.13)
R-871-25W		2.5(0.098)	25W	2.0-3.0(0.19-0.29)	200	440	250-400(9.84-15.75)	

◆R-2003 Spray Distance:250mm(7.87in).Fluid intake:M16x1.5P. Air intake:1/4 PF/NPF.

◆R-871 Spray Distance:200-300mm(7.87-11.81in).Fluid intake:M16x1.5P. Air intake :1/4PF/NPF.