

Ratchet Wrenches



RP-3102A Ratchet Wrenches

- Max Torque : 34 N.M (25 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 128.3 mm (5")



RP-3226 Ratchet Wrenches

- Max Torque : 42 N.M (31 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 165 mm (6 1/2")



RP-3107A1 Ratchet Wrenches

- Max Torque : 95 N.M (70 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 293 mm (11 1/2")



RP-3107B1 Ratchet Wrenches

- Max Torque : 95 N.M (70 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 306 mm (12")



RP-73 Ratchet Wrenches

- Max Torque : 70 N.M (50 ft-lbs)
- Bolt Diameter : 9 mm (3/8")
- Length : 254 mm (10")



MADE IN JAPAN

Model	Square Drive		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm		RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg
RP-3102A	3/8	10	300	34	25	6.3	90	128.3	5	51	2	0.49	1.08
RP-3226	3/8	10	230	42	31	6.3	90	165	6 1/2	71	3	0.50	1.1
RP-3107A1	3/8	10	160	95	70	6.3	90	293	11 1/2	73.6	3	1.26	2.78
RP-3107B1	3/8	10	160	95	70	6.3	90	306	12	71.4	3	1.30	2.87
RP-73	3/8	9	150	70	50	6.3	90	254	10	210	7	1.20	2.65



Ratchet Wrenches

RP-3002A Ratchet Wrenches

- Max Torque : 34 N.M (25 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 128.3 mm (5")



RP-3228 Ratchet Wrenches

- Max Torque : 70 N.M (50 ft-lbs)
- Bolt Diameter : 13 mm (1/2")
- Length : 227 mm (9")



RP-3207A1 Ratchet Wrenches

- Max Torque : 95 N.M (70 ft-lbs)
- Bolt Diameter : 13 mm (1/2")
- Length : 293 mm (11 1/2")



RP-3207B1 Ratchet Wrenches

- Max Torque : 95 N.M (70 ft-lbs)
- Bolt Diameter : 10 mm (3/8")
- Length : 306 mm (12")



RP-74 Ratchet Wrenches

- Max Torque : 70 N.M (52 ft-lbs)
- Bolt Diameter : 9 mm (3/8")
- Length : 254 mm (10")



MADE IN JAPAN

Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-3002A	1/4	10	3/8	300	34	25	6.3	90	128.3	5	51	2	0.49	1.08
RP-3228	1/2	13	1/2	170	70	50	6.3	90	227	9	71	3	1.17	2.58
RP-3207A1	1/2	13	1/2	160	95	70	6.3	90	293	11 1/2	73.6	3	1.26	2.78
RP-3207B1	1/2	10	3/8	160	95	70	6.3	90	306	12	71.4	3	1.30	2.87
RP-74	1/2	9	3/8	150	70	50	6.3	90	254	10	210	7	1.20	2.65

Impact Wrenches



RP-105A Impact Wrenches

- Structure : Hydraulic impulse type
- Max Torque : 35 N.M
(26 ft-lbs)
- Length : 139 mm (5 1/2")



Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-105A	3/8	8	5/16	6100	22~35	16~26	6.3	90	139	5 1/2	68	2	0.84	1.85
RP-106A	3/8	8	5/16	6700	32~50	24~37	6.3	90	139	5 1/2	90.7	3	0.84	1.85
RP-107A	3/8	8	5/16	5400	40~85	30~63	6.3	90	151	6	103	4	0.95	2.09

RP-P6 Impact Wrenches

- Max Torque : 200 N.M
(150 ft-lbs)
- Length : 142 mm (5 5/8")



MADE IN JAPAN

RC-6LSB Impact Wrenches

- Max Torque : 36 N.M (30 ft-lbs)
- Length : 180 mm (7 1/10")



RP-3124T Impact Wrenches

- Max Torque : 406 N.M
(300 ft-lbs)
- Length : 166.5 mm (6 5/8")



Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-P6	3/8	8	8/16	7600	200	150	6.3	90	142	5 5/8	230	8	1.43	3.15
RC-6LSB	3/8	5-6	3/16-1/4	10000	36	30	6.3	90	180	7 1/10	250	9	1.2	2.65
RP-3124T	3/8	13	1/2	9000	406	300	6.3	90	166.5	6 5/8	130	5	1.23	2.71



Impact Wrenches

RP-3203A1 Impact Wrenches

- Max Torque : 81 N.M (60 ft-lbs)
- Length : 118 mm (4 5/8")



RP-3260T Impact Wrenches

- Max Torque : 928 N.M (690 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 191 mm (7 1/2")



RP-3208 Impact Wrenches

- Max Torque : 1085 N.M (800 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 178 mm (7")



RP-3224T Impact Wrenches

- Max Torque : 515 N.M (380 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 166.5 mm (6 5/8")



RP-3241T Impact Wrenches

- Max Torque : 623 N.M (460 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 293 mm (11 1/2")



Model	Square Drive	Bolt Diameter		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-3203A1	1/4	10	3/8	10000	81	60	6.3	90	118	4 5/8	63	2	0.88	1.94
RP-3260T	1/2	16	5/8	7500	928	690	6.3	90	191	7 1/2	133	5	1.94	4.28
RP-3208	1/2	16	5/8	7500	1085	800	6.3	90	178	7	220	7.7	2.62	5.78
RP-3224T	1/2	16	5/8	9000	515	380	6.3	90	166.5	6 5/8	130	5	1.24	2.73
RP-3241T	1/2	16	5/8	8000	623	460	6.3	90	293	11 1/2	184	6	2.63	5.8

Impact Wrenches



RP-3241T-2 Impact Wrenches

- Max Torque : 739 N.M (550 ft-lbs)
- Length : 235 mm (9 1/4")



RP-3250G Impact Wrenches

- Max Torque : 740 N.M (550 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 208 mm (8 3/16")



RP-3238B1 Impact Wrenches

- Max Torque : 680 N.M (500 ft-lbs)
- Bolt Diameter : 16 mm (5/8")
- Length : 113.5 mm (4 1/2")



RP-172P Impact Wrenches

- Max Torque : 430 N.M (320ft-lbs)
- Length : 240 mm(9 1/2")



MADE IN JAPAN

Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-3241T-2	1/2	14	9/16	8000	739	550	6.3	90	235	9 1/4	200	7	2.7	5.95
RP-3250G	1/2	16	5/8	7500	740	550	6.3	90	208	8 3/16	153	5	2.86	6.31
RP-3238B1	1/2	16	5/8	10000	680	500	6.3	90	113.5	4 1/2	140	5	1.40	3.09
RP-172P	1/2	17	3/4	7400	430	320	6.3	90	240	9 1/2	400	14	2.6	5.73



Impact Wrenches

RP-161P Impact Wrenches

- Max Torque : 310 N.M (230 ft-lbs)
- Length : 183 mm (7 3/16")



MADE IN JAPAN

RP-3125A Impact Wrenches

- Max Torque : 1626 N.M (1200 ft-lbs)
- Bolt Diameter : 32 mm (1 1/4")
- Length : 219 mm (8 5/8")



RP-3110C1 Impact Wrenches

- Max Torque : 1490 N.M (1100 ft-lbs)
- Bolt Diameter : 30 mm (1 3/16")
- Length : 227 mm (9")



RP-3110G1 Impact Wrenches

- Max Torque : 1490 N.M (1100 ft-lbs)
- Bolt Diameter : 30 mm (1 3/16")
- Length : 227 mm (9")



Model	Square Drive		Bolt Diameter	Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm			in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm
RP-161P	1/2	16	5/8	4900	310	230	6.3	90	183	7 3/16	240	8	2.45	5.4
RP-3125A	3/4	32	1 1/4	5750	1626	1200	6.3	90	219	8 5/8	195	7	3.15	6.95
RP-3110C1	3/4	30	1 3/16	4985	1490	1100	6.3	90	227	9	168	6	3.61	7.96
RP-3110G1	3/4	30	1 3/16	5500	1490	1100	6.3	90	227	9	167	6	5.40	11.9

Impact Wrenches



RP-190P Impact Wrenches

- Max Torque : 470 N.M (350 ft-lbs)
- Length : 241 mm (9 1/2")

Square Drive

3/4"



MADE IN JAPAN

RP-28P Impact Wrenches

- Max Torque : 1300 N.M (960 ft-lbs)
- Length : 253 mm (10")

Square Drive

3/4"



MADE IN JAPAN

RP-3286 Impact Wrenches

- Max Torque : 1490 N.M (1110 ft-lbs)
- Length : 178 mm (7")

Square Drive

3/4"



RP-3266 Impact Wrenches

- Max Torque : 1898 N.M (1400 ft-lbs)
- Length : 210 mm (8 1/4")

Square Drive

3/4"



Model	Square Drive		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight		
	in	mm		in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg
RP-190P	3/4	19	3/4	5900	470	350	6.3	90	241	9 1/2	400	14	4.23	9.33
RP-28P	3/4	28	1 1/8	4500	1300	960	6.3	90	253	10	520	18	6.81	15.01
RP-3286	3/4	20	13/16	7500	1490	1110	6.3	90	178	7	220	7.7	2.68	5.9
RP-3266	3/4	30	1 1/8	7500	1898	1400	6.3	90	210	8 1/4	300	10.6	4.2	9.26



Impact Wrenches

RP-4185A Impact Wrenches

- Max Torque : 2500 N.M (1850 ft-lbs)
- Length : 277 mm (11")

Square Drive

1"



RP-400PA Impact Wrenches

- Max Torque : 2500 N.M (1850 ft-lbs)
- Length : 285 mm (11 3/16")

Square Drive

1"



MADE IN JAPAN

RP-381P Impact Wrenches

- Max Torque : 2500 N.M (1850 ft-lbs)
- Length : 266 mm (10 1/2")

Square Drive

1"



MADE IN JAPAN

RP-452P Impact Wrenches

- Max Torque : 3000 N.M (2210 ft-lbs)
- Length : 322 mm (12 3/4")

Square Drive

1"



MADE IN JAPAN

Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-4185A	1	33	1 3/16	4800	2500	1850	6.3	90	277	11	270	10	10.2	22.49
RP-400PA	1	41	1 5/8	4700	2500	1850	6.3	90	285	11 3/16	900	32	10.8	23.81
RP-381P	1	38	1 1/2	4500	2500	1850	6.3	90	266	10 1/2	700	25	10.3	22.71
RP-452P	1	45	1 3/4	2900	3000	2210	6.3	90	322	12 3/4	850	30	14.3	31.53

Impact Wrenches



RP-45S-2 Impact Wrenches

- Max Torque : 3200 N.M (2360 ft-lbs)
- Length : 632 mm (25")



MADE IN JAPAN

RP-400SA Impact Wrenches

- Max Torque : 2300 N.M (1700 ft-lbs)
- Length : 516 mm (20 5/16")



Inside lever

MADE IN JAPAN

RP-400SA-2 Impact Wrenches

- Max Torque : 2400 N.M (1770 ft-lbs)
- Length : 350 mm (13 3/4")



Inside lever

MADE IN JAPAN

RP-535S Impact Wrenches

- Max Torque : 3100 N.M (2290 ft-lbs)
- Length : 632 mm (25")



Inside lever

MADE IN JAPAN

Model	Square Drive			Free Speed RPM	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in		N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-45S-2	1	45	1 3/4	3200	3200	2360	6.3	90	632	25	850	30	17.1	37.7
RP-400SA	1	40	1 5/8	4400	2300	1700	6.3	90	516	20 5/16	750	27	12.1	26.68
RP-400SA-2	1	41	1 5/8	4400	2400	1770	6.3	90	350	13 3/4	750	27	10.6	23.37
RP-535S	1	46	1 3/4	3000	3100	2290	6.3	90	632	25	750	27	18.2	40.12



RP-535S-2 Impact Wrenches

- Max Torque : 3200 N.M (2360 ft-lbs)
- Length : 632 mm (25")



MADE IN JAPAN

RP-551S Impact Wrenches

- Max Torque : 5500 N.M (4060 ft-lbs)
- Length : 520 mm (20 1/2")



MADE IN JAPAN

RP-551SA Impact Wrenches

- Max Torque : 5500 N.M (4060 ft-lbs)
- Length : 553 mm (21 3/4")



MADE IN JAPAN

Model	Square Drive		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight		
	in	mm		in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg
RP-535S-2	1	46	1 3/4	3000	3300	2440	6.3	90	444	17 1/2	750	27	18.2	40.12
RP-551S	1 1/2	55	2 3/16	3600	5500	4060	6.3	90	520	20 1/2	870	31	17.8	39.24
RP-551SA	1 1/2	55	2 3/16	3600	5500	4060	6.3	90	553	21 3/4	870	31	18	39.68