

Straight Shape Screwdriver



RC-4.5 Straight Shape Screwdriver



RC-4.5S Straight Shape Screwdriver



RC-5S Straight Shape Screwdriver



RC-5SS Straight Shape Screwdriver



RC-5.8 Straight Shape Screwdriver



RC-5.8S Straight Shape Screwdriver




Model	Tips Specification	Bolt Diameter		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RC-4.5	1/4	4-5	5/32-3/16	9000	14.5	11	6.3	90	176	7	220	8	0.7	1.54
RC-4.5S	1/4	4-5	5/32-3/16	9000	14.5	11	6.3	90	176	7	220	8	0.7	1.54
RC-5S	1/4	3-5	1/8-3/16	9000	12.5	9	6.3	90	156	6 1/16	220	8	0.6	1.32
RC-5SS	1/4	3-5	1/8-3/16	9000	12.5	9	6.3	90	156	6 1/16	220	8	0.6	1.32
RC-5.8	1/4	4-5	5/32-3/16	9000	18	13	6.3	90	180	7 1/16	220	8	0.7	1.54
RC-5.8S	1/4	4-5	5/32-3/16	9000	18	13	6.3	90	190	7 1/16	220	8	0.7	1.54




Straight Shape Screwdriver

RC-6H Straight Shape Screwdriver



RC-8H Straight Shape Screwdriver




RC-9H Straight Shape Screwdriver




RC-10H Straight Shape Screwdriver



RP-S6L Air Screwdriver



RP-10L Air Screwdriver



MADE IN JAPAN

Model	Tips Specification	Bolt Diameter		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RC-6H	1/4	6	1/4	8500	23.5	17	6.3	90	200	7 7/8	250	9	1	2.2
RC-8H	1/4	6	1/4	8500	28	21	6.3	90	202	8	250	9	1	2.2
RC-9H	1/4	6-8	1/4-5/16	8500	36	27	6.3	90	202	8	250	9	1	2.2
RC-10H	1/4	8-10	5/16-3/8	9500	42	31	6.3	90	200	7 7/8	250	9	1	2.2
RP-S6L	1/4	8	5/16	8000	-	-	6.3	90	212	8 3/8	310	11	1.33	2.93
RP-10L	1/4	6-8	1/4-5/16	8000	60	44	6.3	90	217	8 1/2	130	5	1.3	2.87

90°Screwdriver / Pistol Shape Screwdriver



RP-418B Torque Control Screwdriver



- 1.External torsion operation adjustment simple, it can start once you press it.
- 2.Preeise torsion Control , torsion control with high accuracy , And the torsion very stable.
- 3.When it reach the setting torsion value , the torsion contorl valve will be shut off air alltomatically The screwdriver also stop working automatically.

RC-240-90 90°Screwdriver




RP-P6L Pistol Shape Screwdriver



MADE IN JAPAN

RP-8008A Pistol Shape Screwdriver



RP-8018A Pistol Shape Screwdriver



RC-6LS Pistol Shape Screwdriver



RC-6LSP Pneumatic Screwdriver



Model	Tips Specification		Bolt Diameter		Free Speed	Max Torque		Air Pressure		Length		Air Consumption		Weight	
	in	mm	in	mm	RPM	N.M	ft-lbs	kg/cm ²	psi	mm	in	l/min	cfm	kg	lbs
RP-418B	1/4	2.5-4	1/10-5/32	1100	1.6	1	6.3	90	230	9	200	7	0.67	1.48	
RC-240-90	1/4	4-5	5/32-3/16	5500	14.5	11	6.3	90	210	8 1/4	220	8	0.9	1.98	
RP-P6L	1/4	8	5/16	7600	-	-	6.3	90	212	8 3/8	340	12	1.47	3.24	
RP-8008A	1/4	6.4	1/4	550	12	9	6.3	90	215	8 1/2	140	5	1.28	2.82	
RP-8018A	1/4	6.4	1/4	1800	12	9	6.3	90	215	8 1/2	140	5	1.23	2.71	
RC-6LS	1/4	5-6	3/16-1/4	10000	36	27	6.3	90	180	7 1/10	250	9	1.2	2.65	
RP-6LSP	1/4	8-10	5/16-3/8	9800	45	33	6.3	80	155	6 1/10	250	9	2.5	5.51	